Curl

simple curl GET

```sh
curl "https://api.onesignal.com"
```

simple curl POST

```sh
curl -X "POST" "https://api.onesignal.com"
```

curl with json request and header

```sh
curl -X "POST" "https://iems.kpdn.gov.my/oauth/token" \
     -H 'Content-Type: application/json; charset=utf-8' \
     -d $'{
  "client_id": "3",
  "scope": "ecoss",
  "client_secret": "v3v0kqaUPYkxO7tl3FprWcbD3pzyk7EgvnEBzLmk",
  "grant_type": "client_credentials"
}'```

curl with full url

```sh
curl
"https://familyhub.lppkn.gov.my/index.php/epms_api/LPPKNReportGateway?token=HEgAtuOHunGq
miMEVDUMjhTAYJRxyM&laporan=1004&tahun=2023&sukuan=1"
```
curl with hidden method (laravel)
```sh
curl -X "POST" "http://10.29.59.97/gps/gpss/50/budgets"
     -d $'{
     "_method": "PATCH",
  "test": "somthing"
}'
```

curl with auth token in header
```

```sh
curl -X "POST" "http://10.29.59.97/gps/gpss/50/budgets" -H "Content-Type: application/x-www-form-urlencoded" -d "_method=PATCH&token=bgl2TOaY5IdSQRHQDEPKvZd1Y79N66fFNOaV4E9P"
```

Revision #1
Created 12 May 2025 08:57:16 by Editor
Updated 12 May 2025 08:57:24 by Editor